

ICON™ Wiper Blades

Windshield Wiper Program



Windshield curvatures and aerodynamics have become increasingly complex over the years. Wiper blades need to bridge the contact gap between the wiping edge and the windshield for maximum wiping performance.

- 1 ClearMax 365™, an exclusive, patented rubber technology** combines a soft rubber core with a powder-coated shell.
 - Protects the wiping edge from ozone deterioration, snow, sleet, rain, and road debris for longer life
 - Reduces wiping friction for quieter performance
 - Resists contaminants such as fluids, salts, insects and other road debris for streak free visibility
- 2 Dynamic Fit™ technology**
 - Optimized beam bending technology adapts to the entire curve of the windshield
- 3 Asymmetrical aerodynamic flexible spoiler**
 - Distributes uniform downward force along the entire blade to hold it firmly to the windshield
- 4 Weather-shield double-locking connector**
 - Offers easy and secure installation
- 5 Pre-installed weather shield connector system**
 - Protects arm connection from ice and snow build-up

Hook Arm Product Range Coverage

Length	MKT #	% Coverage
13	13A	1.2%
15	15A	0.9%
16	16A	4.3%
17	17A	2.9%
18	18A	7.6%
19	19A	4.5%
20	20A	9.4%
21	21A	3.5%
22	22A	17.8%
24	24A	7.8%
26	26A	10.8%
28	28A	1.8%
28	28B	0.2%
Hook Total		72.8%



ICON™ Wiper Blades

Windshield Wiper Program

ICON™ Wiper Blades OE Fitment Solutions

The Simple Solution to OE Fitment

Bosch continues its innovation and leadership with the ICON™ OE Multi-Clip connector. Designed to tackle the ever-increasing number of top-lock and side-lock applications in the market, the Multi-Clip features a flexible connector system, simplifying the installation process for all types of vehicles.

Designed with Total Performance in Mind

This Multi-Clip connector design not only offers outstanding performance, it also provides a clean, attractive look that can complement any vehicle.

Most Popular OE Connection Types Covered by ICON ClearMax 365™

9x3 U-Hook 	9x4 U-Hook 	Side Lock 	Side Lock Narrow 
Top Lock 	Top Lock Narrow 	Pinch Tab 	Top Lock Denso 

**Requires specialty adapter.*

OE Arm Product Range Coverage

Length	MKT #	% Coverage
13	13OE	0.2%
15	15OE	0.3%
17	17OE	0.5%
18	18OE	0.4%
19	19OE	0.7%
20	20OE	1.7%
21	21OE	1.2%
22	22OE	4.8%
24	24OE	3.0%
26	26OE	2.5%
28	28AOE	1.2%
28	28BOE	0.8%
OE Total		17.2%

