

EU Safety Data Sheet
Trade name: Thewalt T 16
Date of revision: 02.05.2005
Page 1 of 6

Thewalt S.A.

POLYPHALT®
EVALT®

EU Safety Data Sheet

according to 91/155/EEC

Trade name	Thewalt T 16		
Name of substance / preparation	Naphtha (petroleum), hydrotreated heavy with Hitec 536 and Ionol CP		
Chemical characterization	Aliphatic and cycloaliphatic hydrocarbon mixture, which is a complex substance produced from petroleum, with Hitec 536 and Ionol CP		
Use of substance / preparation	Suitable for general industrial use.		
Company name	Thewalt S. A. 26, Boulevard Royal L-2449 LUXEMBOURG		
Emergency number	during regular business hours outside of regular business hours or contact your local emergency number for intoxications	Phone: +49 (0) 6 81 - 9 68 10- 0 Fa. Thewalt Saarbrücken Phone: +49 (0) 6 81 - 9 68 10- 0 Fax: +49 (0) 6 81 - 9 68 10-20	

Name	Naphtha (petroleum), hydrotreated heavy		
CAS number	64742-48-9		
EINECS number (EC No)	265-150-9		
Classification of product	<u>Symbols</u>	<u>R-phrases</u>	
	-	10	
	Xn	65	
	-	66	

Annex I to Directive 67/548/EEC:

REF H: Self-classification for non-listed properties.
REF P: Benzene concentration < 0.1 % of weight.
REF 4: Kinematic viscosity at 40°C < 7 mm²/s.

Hazardous components			Content	Symbols	R-phrases
EINECS No	CAS No.	Name			
-	-	Hitec 536	0,1 %	XI	43
204-881-4	128-37-0	2,6-di-tert-butyl-p-cresol (Ionol CP)	0,1 %	-	-

Classification

Flammable. Harmful; may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Additional warnings of hazards to human health and the environment

Danger of electrostatic charging. Explosive vapour / air mixtures may be generated.

EU Safety Data Sheet
Trade name: Thewalt T 16
Date of revision: 02.05.2005
Page 2 of 6

thewalt S.A.

POLYPHALT®
EVALT®

General instructions	Remove victim from danger zone, without exposing yourself to any personal risk. Remove wetted clothing and shoes and clean items before using them again.
After inhaling	Move victim outside into fresh air, if breathing is irregular or has stopped, perform artificial respiration. Immobilise victim and assure immediate attendance by a physician.
After skin contact	Wash off thoroughly with soap and water - apply cream -.
After eye contact	Rinse off with water for long period of time - see a doctor.
After swallowing	Do not give victim any food or drink. Do NOT induce vomiting. Immobilise victim and call a doctor.
Symptoms and effects	Product may cause headache, dizziness, nausea, loss of consciousness and dry skin. Disorders of the central nervous system are possible as well. Also see item 11.
Instructions for attending physician	Prolonged and/or repeated exposure may cause skin discomfort and inflammation (dermatitis). In case of swallowing followed by vomiting, material may be aspirated into the lungs - possibly leading to pulmonary edema (wet lung).

Suitable extinguishing agents	Foam, dry extinguishing agents, carbon dioxide, fine dispersion of water spray (mist)
Unsuitable extinguishing agents	Water, full spray
Special hazards arising from the substance or the preparation itself, its products of combustion or gases generated	Incomplete combustion generates carbon monoxide. Vapours are heavier than air and will spread across the ground, with igniting possible over long distances. "Floats" up and may re-ignite.
Protective gear / equipment	Full-protection suit, respirator with self-contained air supply
Risk-prone containers	Cool with water spray.

Personal-related precautions	Avoid skin and eye contact. Do not inhale vapours / aerosols. Eliminate all potential sources of ignition. Remove all personnel not required on site from danger zone. Take precautions against electrostatic charging. Seal leaks, without exposing yourself to personal risk. Use personal protective clothing/equipment - also see item 8 -.
Environmental precautions / cleaning procedures	<p>Try to prevent product from entering into sewer lines, bodies of water and soil. Notify fire department or police if product has entered bodies of water or sewer lines, or has contaminated soil and plants. Contain liquid by an appropriate barrier, e.g. sand, and pump into a specially marked container. Absorb any residues using absorbing materials (e.g. sand, oil binding agents and similar means of absorption). Properly dispose of in compliance with environmental regulations.</p> <p>In case of inadvertent release (spillage) on waterways, keep barge, boat traffic, etc. at appropriate distance. Notify harbour/ river police, coast guard, etc. and prevent general public from getting close to the scene. If possible, seal leaks, without exposing yourself to personal risk. Contain liquid, if possible. Remove product from water surface by skimming or using suitable means of absorption. In case of spillage in rivers, etc., coordinate with competent authorities to allow product to sink to the bottom and/or use suitable deflocculation agents.</p>

EU Safety Data Sheet
Trade name: Thewalt T 16
Date of revision: 02.05.2005
Page 3 of 6

Thewalt S.A.

POLYPHALT®
EVALT®

Mandling

Handling safety instructions

Avoid skin and eye contact and wear personal protective gear. Avoid inhalation of vapours / aerosols. Inside closed rooms or when filling or emptying containers, assure sufficient ventilation during operations (use local exhaust/suction system, if needed/available).

In laboratories, product should only be handled underneath exhaust fan system (GLP). Use suitable precautions to prevent product from entering sewer lines, bodies of water and soil.

Fire and explosion protection instructions

Keep away from sources of ignition and heat - do not smoke - Take precautions against electrostatic charging and explosion (see relevant chemical industry/trade association publications, e.g. BG-Chemie). Any fire protection measures required must be coordinated with competent authorities.

Miscellaneous information

Empty containers may still contain product residues and thus harbour respective risks - continue to take appropriate precautions.

Storage

Requirements to be met by storage facilities and containers

Keep container sealed tightly. Store at room temperature. May react with air to generate explosive mixture. Keep away from food and beverages. Type and quality of tanks and storage facilities must be coordinated with competent authorities.

Combined storage instructions

Do not store together with strong oxidation agents.

Suitable materials

C-steel, high-grade (stainless) steel, polyethylene, polypropylene, polyester, teflon

Unsuitable materials

Natural rubber, butyl rubber, EPDM, polystyrene

Temperature class (Germany)

T 3

Critical exposure values (German legislation; if applicable consult national legislation)

Name/designation	Type	Peak value	Critical value
De-aromatized hydrocarbon mixtures	TRGS 900/901 (Group 1)	4	200 ml/m ³

Boundary values for Hitec 536 (content: 0.1%) and Ionol CP (content: 0.1%) are not available.

Limitation and monitoring of workplace exposure

Local exhaust systems or mechanical rarefaction ventilation systems are recommended to keep product concentration below the recommended exposure limits. Local exhaust systems can also be used to monitor process emissions directly at the source.

Further information can be obtained from the following sources:

- BG-Chemie
- Zentralstelle für Arbeitsschutz in Kassel
- TRGS 400: Verzeichnis akkreditierter Messstellen
- ACGIH (American Conference of Governmental Industry Hygienists)

Personal protective gear / equipment

Respiratory protection

In case of risk that the stated boundary values may be exceeded, the following respiratory protection is recommended: filter in gas mask for org. gases and vapours (type A).

Hand protection

Protective gloves made of nitrile oder Viton, e.g. Camatril Velours 730 (nitrile) or Vitejekt 890 (Viton) made by KCL. (permeation time > 480 min)

Eye protection

Tightly sealing goggles with side protection.

Body protection

Hydrocarbon solvent-resistant protection suit and safety shoes

General protection and hygienic measures

The choice of personal protection gear depends on the danger emanating from the product, the respective workplace as well as the type of handling. All personnel entering the area in which the product is handled must - as a minimum - be wearing goggles with side protection. Avoid skin and eye contact. Do not inhale vapours/aerosols. Do not eat, drink or smoke while working. Change wetted clothing.

EU Safety Data Sheet
Trade name: Thewalt T 16
Date of revision: 02.05.2005
Page 4 of 6

thewalt S.A.

POLYPHALT®
EVALT®

General information

Physical / aggregate state liquid
Colour colourless, clear
Odour typically, mild

Critical information on health / environmental protection and safety

Melting point	< - 20 °C	
Boiling point	155 / 188 °C	DIN EN ISO 3405
Flash point	40 °C	DIN EN ISO 13736
Explosion limits	0,6 - 7,0 vol. %	
Ignition temperature	> 200 °C	DIN 51794
Vapour pressure at 20 °C	2 hPa	DIN EN 12
Vapour pressure at 50 °C	15 hPa	DIN EN 12
Density at 15 °C	772,0 kg/m³	DIN 51757
Solubility in water at 20 °C	insoluble	
Distribution coefficient n-octanol / water	4,9 - 6,5 (estimated)	log POW
Kinematic viscosity at 20 °C	1,3 mm²/s	DIN 51562
Kinematic viscosity at 40 °C		DIN 51562
Evaporation rate (ether = 1)	60	DIN 53170

Miscellaneous information

Hygroscopic no
Molecular weight app. 142 g/mol (calculated)

Stability

Stable under normal conditions.

Conditions to be avoided

Flames, sparks, heat

Substances to be avoided

Strong oxidizing agents

Hazardous products of instability / decomposition

None known

Basis of evaluation

Evaluation has been derived from data material on hydrocarbons of single components and / or similar products.

Acute toxicity data

LD ₅₀ , oral, rat	> 15.000 mg/kg
LC ₅₀ , inhalative, rat	> 6,1 mg/l (4 hours)
LD ₅₀ , dermal, rabbit	> 3.000 mg/kg
Skin irritation, EU value, rabbit	low [minimal], no rating
Skin sensitization, human and / or guinea pig	no sensitization
Eye irritation, acc. to Draize, rabbit	low [minimal], no rating

After swallowing

Swallowing, particularly if followed by vomiting, may lead to pulmonary damage - pneumonia - pulmonary edema (wet lung).

After inhaling

Inhalation of vapours exceeding the workplace-related limit (subject to monitoring) should be avoided. High concentrations of vapour / aerosol have a numbing effect, possibly resulting in disorders of the central nervous system.

After skin contact

Frequent or prolonged dermal contact may cause skin to lose oil, resulting in skin inflammation (dermatitis).

After eye contact

Causes eye discomfort. Under normal conditions, eye tissue will not be damaged.

Mutagenicity

No mutagenicity

EU Safety Data Sheet
Trade name: Thewalt T 16
Date of revision: 02.05.2005
Page 5 of 6

thewalt S.A.

POLYPHALT®
EVALT®

Basis of evaluation	Evaluation has been derived from data material on hydrocarbons of single components and / or similar products.
Acute eco-toxicity, crustaceans (Gammarus locusta)	LL50: > 100 mg/l (96 hours)
Mobility	Product floats on the surface of water and water solubility is minimal, it is adsorbed by the soil and not mobile.
Persistence / degradability	Product is easily bio-degradable (Manometric Respirometry).
Bioaccumulation	Potential for bioaccumulation exists.
Miscellaneous Information	No long-term damaging effects for aquatic organisms are expected. Product does not contain any absorbable organic halogen compounds (AOX).
Water hazard class (Germany)	1 (List classification according to VwVwS)

Product	Disposal instructions refer to the pure, unmodified product. If possible, recondition product, otherwise incinerate in officially approved incinerating plant. Allocation of the EAK-Code (European Waste Catalogue) is the responsibility of the user.
Packaging w/o prior cleaning	WARNING! Even empty containers (with all residues removed) remain contaminated and must either be properly disposed of by trained personnel or subjected to an approved reconditioning process.

Surface / land transportation ADR / RID	
Class	3
Packing group	III
UN No.	3295
Classification code	F 1
Hazard ID No.	30
Hazardous label	3
Name / designation used in shipping documents	UN 3295, HYDROCARBONS, LIQUID, N.O.S., 3, III
Sea vessel transport IMDG Code / GGVSee	
Class	3
Packing group	III
UN No.	3295
Marine Pollutant	no
EMS No.	F-E, S-D
Hazard ID	3
Additional ID	
Proper shipping name	HYDROCARBONS, LIQUID, N.O.S. (Isodecane & n-Decane), 3, UN 3295, III, (40 DegC c.c.)
Air transport (ICAO-TI and IATA-DGR)	
Class	3
Packing group	III
UN No.	3295
Proper shipping name	HYDROCARBONS, LIQUID, N.O.S. (Isodecane & n-Decane)

EU Safety Data Sheet
 Trade name: Thewalt T 16
 Date of revision: 02.05.2005
 Page 6 of 6

thewalt S.A.

POLYPHALT®
 EVALT®

Marking acc. to current EC Directive and / or Gefahrstoffverordnung (Germany):

Hazard symbol / s	Xn -	Harmful
Name / designation used on label	Naphtha (petroleum), hydrotreated heavy with Hitec 536 and Ionol CP	
R - phrases	10 -	Flammable.
	65 -	Harmful: may cause lung damage if swallowed.
	66 -	Repeated exposure may cause skin dryness or cracking.
S - phrases	23 -	Do not breathe gas/fumes/vapour/spray.
	24 -	Avoid contact with skin.
	43 -	Use foam, dry extinguishing agent, CO2 or possibly water aerosol to extinguish.
	62 -	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
National regulations	Product is subject to VOC control tax.	
VOC Directive (Switzerland)	Product is considered a "volatile organic compound"	
31. BmSchV (Germany)	1 (List classification according to VwVwS)	
WGK (Germany)	2710 11 21	
HS - Code		

Warnings pertaining to hazardous ingredients / components addressed in Item 2:

Hitec 536

May cause sensitisation by skin contact. (43)

2,6-di-tert-butyl-p-cresol (Ionol CP)

This information provided in this Safety Data Sheet is based on our knowledge, know-how and experience at the time of publication. The information refers strictly to the product per se. If the product is mixed with other materials or subjected to any kind of treatment or processing the information as stated herein may no longer be valid. THEWALT S.A. does not guarantee the information stated herein to be free from errors and/or complete, nor does this information constitute or imply any promises or assurances.